

GEAR OILS FOR THE FOOD, ALCOHOL AND TOBACCO INDUSTRIES							
Product	Base oil	Anti-wear additive	Viscosity 40 °C (mm ² /s)	Viscosity index	Pourpoint (°C)	Application	Application in Greek
Optileb GT 100	PAO	EP/AW	100	148	-42	Gear lubricants for spur gears, angular gears and worm gears, for gear drives on agitators, variable speed chain gearboxes, slide and roller bearings along with pumps and closed circulating systems. NSF-H1 registered.	Λιπαντικά γραναζιών για γρανάζια ευθείας οδόντωσης, γωνιακά γρανάζια και γρανάζια τύπου σκουληκιού, για συστήματα γραναζιών σε αναδευτήρες, κιβώτια ταχυτήτων μεταβλητής ταχύτητας, ρουλεμάν ολισθήσης και κυλίνδρων, καθώς και για αντλίες και κλειστά κυκλικά συστήματα. Καταχωρημένα NSF-H1.
Optileb GT 150	PAO	EP/AW	150	149	-42		
Optileb GT 220	PAO	EP/AW	220	157	-36		
Optileb GT 320	PAO	EP/AW	320	150	-33		
Optileb GT 460	PAO	EP/AW	460	151	-27	Gear oils for use in worm gears, spur gears, bevel gears and planetary gears. NSF-H1 registered.	Λιπαντικά γραναζιών για χρήση σε γρανάζια σκουληκούς αλλά και ευθείας οδόντωσης, κωνικά γρανάζια και πλανητικά γρανάζια. Καταχωρημένα NSF-H1.
Optileb GT 1800/220	PG	EP/AW	220	235	-33		
Optileb GT 1800/460	PG	EP/AW	460	255	-30		