

TURBINE OILS						
Product	Base oil	Viscosity 40 °C (mm²/s)	Viscosity index	Pourpoint (°C)	Application	Application in Greek
Perfecto X 32	Spec. mineral oil	32	112	-15	Alloyed turbine oils of the latest additive and base-oil technology for lubricating steam and gas turbines and their control systems. They fulfil the requirements of "lubricants and control oils L-TG" of DIN 51 515 Part 2 and those of ISO 8068.	Λιπαντικά αεροστροβίλων με μίγμα, βασισμένα στην τελευταία τεχνολογία πρόσθετων και βάσης, για τη λίπανση ατμοστροβίλων και αεροστροβίλων καθώς και των συστημάτων ελέγχου τους. Πληρούν τις απαιτήσεις των "λιπαντικών και ελαίων ελέγχου L-TG" του DIN 51 515 Μέρος 2 και του ISO 8068.
Perfecto X 46	Spec. mineral oil	46	112	-15		
Perfecto X 68	Spec. mineral oil	68	112	-12		
Perfecto XEP 32	Spec. mineral oil	32	112	-15	EP-alloyed turbine oils of the latest additive and base-oil technology for lubricating steam and gas turbines as well as their control systems. They fulfil the requirements of "lubrication and control oils L-TG with anti-wear protection" according to DIN 51 515 Part 2, the requirements according to BS 489 as well as ISO 8068.	Λιπαντικά αεροστροβίλων με μίγμα EP, βασισμένα στην τελευταία τεχνολογία πρόσθετων και βάσης, για τη λίπανση ατμοστροβίλων και αεροστροβίλων καθώς και των συστημάτων ελέγχου τους. Πληρούν τις απαιτήσεις των "λιπαντικών και ελαίων ελέγχου L-TG με προστασία κατά της φθοράς" σύμφωνα με το DIN 51 515 Μέρος 2, τις απαιτήσεις του BS 489 καθώς και του ISO 8068.
Perfecto XEP 46	Spec. mineral oil	46	112	-15		
Perfecto XEP 68	Spec. mineral oil	68	112	-12		